



DS S 2F - Foam Station

Article #	700100
Maximum inlet pressure, water	30 bar / 450 psi
Maximum temperature, inlet water	70°C
Max. temperature for foaming	50°C
Air pressure required	3-6 bar
Water inlet	1/2"
Air inlet	1/4"
Max. length of discharge hose	35 meter
Type of discharge hose	Process Cleaners A/S
Quick couplings	Standard
Flush nozzle	Standard
Foam nozzle	Standard
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 litre per minute
Water for flushing	30 litre per minute
Size: width X height X depth	200 x 300 x120



DS S 3F - Foam Station Plus

Article #	700200
Maximum inlet pressure, water	30 bar / 450 psi
Maximum temperature, inlet water	70°C
Max. temperature for foaming	50°C
Air pressure required	3-6 bar
Water inlet	1/2"
Air inlet	1/4"
Max. length of discharge hose	35 meter
Type of discharge hose	Process Cleaners A/S
Quick couplings	1/2"
Flush nozzle	Standard
Disinfections nozzle	Standard
Foam nozzle	Standard
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 litre per minute
Water for flushing	30 litre per minute
Size: width X height X depth	500 x 300 x130