



**PC R5 2F – Pump Center with 2 Functions**

Article #	720502
Pump pressure, water	20 bar over inlet pressure
Water for flushing	10-100 liter per minute
Max. inlet pressure, water	5 bar / 75 psi
Max. temperature, inlet water	70°C
Max. temperature for foaming	50°C
Motor capacity	5,5 kW
Power supply	3 x 380 VAC or special
Protection, electrical supply	12 Amp
Weight	170 kg
Water inlet	1 ½"
Flow switch min. start flow	10 liter per minute
Air pressure required	3-6 bar
Max. length of discharge pipe	up to 35 meter, accessory
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 liter per minute
Size: width X height X depth	750 x 1700 x 350

**PC R8 2F - Pump Center with 2 Functions**



Article #	720802
Pump pressure, water	20 bar over inlet pressure
Water for flushing	10-150 liter per minute
Max. inlet pressure, water	5 bar / 75 psi
Max. temperature, inlet water	70°C
Max. temperature for foaming	50°C
Motor capacity	7,5 kW
Power supply	3 x 380 VAC or special + 0 + earth
Protection, electrical supply	16 Amp
Weight	190 kg
Water inlet	1 ½"
Flow switch min. start flow	10 liter per minute
Air pressure required	6-8 bar / 90-120 psi
Max. length of discharge pipe	up to 35 meters, accessory
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 liter per minute
Size: width X height X depth	750 x 1700 x 350

