



**PA S 3F - Automatic Foam Unit**

Article #	740103
Max. inlet pressure, water	30 bar / 450 psi
Max. temperature, inlet water	70°C
Max. temperature for foaming	50°C
Air pressure required	6-8 bar / 90-120 psi
Voltage	24 V. DC
Water inlet	1"
Air inlet	1/4"
Max. length of discharge pipe	35 meter
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 litre per minute
Water for flushing	Up to 150 litre per minute
Size: width X height X depth	500 x 700 x 350



**PA R5 3F - Automatic Pump Center**

Article #	740503
Pump pressure, water	16 bar over inlet pressure
Water for flushing	10-100 liter per minute
Max. inlet pressure, water	5 bar / 75 psi
Max. temperature, inlet water	70°C
Max. temperature for foaming	50°C
Motor capacity	5,5 kW
Power supply	3 x 380 VAC or special + 0 + earth
Protection, electrical supply	16 Amp
Weight	170 kg
Water inlet	1 1/2"
Flow switch min. start flow	10 liter per minute
Air pressure required	6-8 bar / 90-120 psi
Max. length of discharge pipe	35 meter
Product concentration	1-8%, dep. on viscosity
Foam spraying water usage	8-12 liter per minute
Size: width X height X depth	1600 x 1500 x 350