



PA R8 3F - Automatic Pump Center with 3 Functions

Article #	740803
Pump pressure, water	16 bar over inlet pressure
Water for flushing	10-150 litre per minute
Maximum inlet pressure, water	5 bar / 75 psi
Max. temperature, inlet water	70°C
Max. temperature for foaming	50°C
Motor capacity	7,5 kW
Power supply	3 x 380 VAC or special + 0 + earth
Protection, electricity supply	20 Amp
Weight	190 kg
Water inlet	1 1/2"
Flow switch minimum start flow	10 litre per minute
Air pressure required	6-8 bar / 90-120 psi
Max. length of discharge pipe	35 meter
Product concentration	2 x 1-8%, dep. on viscosity
Foam spraying water usage	8-12 litre per minute
Size: width X height X depth	1600 x 1500 x 350



PA Special - Automatic Pump Center

Article #	740000
Pump pressure, water	16 bar over inlet pressure
Water for flushing	depend on size of pump
Maximum inlet pressure, water	10 bar / 150 psi
Maximum temperature, inlet water	70°C
Motor capacity	-
Power supply	3 x 380 VAC or special + 0 + earth
Protection, electricity supply	-
Weight	-
Water inlet	-
Flow switch minimum start flow	10 litre per minute
Air pressure required	6-8 bar / 90-120 psi
Maximum length of discharge pipe	35 meter
Product concentration	2 x 1-8%, dep. on viscosity
Foam spraying water usage	8-12 litre per minute
Size: width X height X depth	-